



Standard Wheelchair

Model #: _____
Serial #: _____
Date: _____

Provider Name: _____
Phone #: _____
Contact Person: _____

Setting up your equipment:


- The delivery technician will assist in evaluating your home environment for possible obstacles.
- The delivery technician will set up your wheelchair.
- Never allow anyone except the designated patient to operate the wheelchair.

Using your equipment:

Have your delivery technician explain how to:

- Remove and adjust footrest/leg rest (Diagram 1)
- Fold wheelchair to the most compact position (Picture 1)
(See also Special Procedures)
- Engage wheel locks for transfer
- Load wheelchair into car
- Remove armrests (if detachable)
- Self propel the wheelchair using the proper techniques

Diagram 1



Picture 1



Frequent replacement items:

(Replace as needed)

- Tires
- Upholstery (including seat, back, and armrests)
- Undue negligence to chair could be charged to beneficiary.

Maintenance:

- General Cleaning (normal household cleaners are acceptable) weekly.
- Wheels and tires should be checked for cracks, wear, and for proper inflation monthly.
- Adjust wheel locks to compensate for tire wear periodically. (save tag attached)
- Check upholstery for sagging, rips or tears monthly.
- Check the spokes of the wheels for loose or broken spokes. Call dealer immediately for replacement.
- If the wheels are plastic, inspect them for breakage or wear periodically.
- Clean bearings frequently and keep them free of moisture.



Special Procedures:

- **Unfolding**
 - Begin by grasping the wheelchair's push handle that is closest to you.
 - Tilt the wheelchair towards you. This will cause the opposite wheel and caster to raise off the ground.
 - Push down on the top of the seat rail closest to you until chair is fully opened.
 - Engage both wheel locks.
 - Open the legrest to transfer into wheelchair.
- **Folding**
 - With the wheel locks engaged, swing the legrest to the front of the wheelchair.
 - Rotate the footplates upward to the vertical position.
 - Grabbing both the front and back edges of the seat upholstery, lift up to close. (Picture 1)
- **Tilting**
 - An assistant must grasp a non-removable part of the back of the wheelchair and have the occupant lean back. This will aid in maintaining center of balance.
 - There must be two assistants present when approaching a curb.
 - The first assistant stands on the curb with the rear wheels against the curb.
 - Turn the anti-tippers. This will cause the anti-tip wheels to point up.
 - Tilt the chair backward until the balance point is achieved.
 - The second assistant stands at the front of the wheelchair and lifts it upward (grasping a non-removable part of the frame) as the first assistant pulls the rear wheel up over the curb.
 - Do not allow front of chair to tip back to the ground until both rear and front of chair clears the edge of the curb.
- **General Wheelchair Handling**
 - **Self**
 - Maintain your balance at all times.
 - Avoid reaching beyond a comfortable range. Extending your center of gravity too much could cause the wheelchair to tip.
 - Do not lean backwards over the top of the back of your wheelchair. Rather, reach back only as far as you can without adjusting your position in your chair.
 - **Attendant**
 - Keep back straight and knees bent when maneuvering over a curb or single step.
 - Inform wheelchair occupant before making any maneuvers with his/her chair.
 - Remind occupant to lean back when tilting the wheelchair.

Safety Issues:

- Wheellocks are not designed to be used as brakes.
- Maximum user weight for this wheelchair is ____ lbs.
- Always engage wheellocks when transferring in or out of the chair.
- Never step on footplates. The chair will tip forward and could cause injury.
- Always remove or swing away front riggings when transferring in or out of the wheelchair.
- Avoid or use caution on wet, slippery or uneven surfaces.
- Do not ride escalators while seated in a wheelchair, instead use the elevator.
- Do not reach beyond the seat area because you could lose your balance, and your wheelchair could tip over.
- Never hold onto removable parts when lifting a wheelchair, injury could occur if removable parts separate from the chair during lifting.

Please contact your equipment provider for any questions, adjustments, or repairs.

Your local provider:



©Copyright The VGM Group 2002
B.L.U.E. Sheet photos, drawings, and text courtesy of
Golden Technologies, Invacare, Leisure-Lift, Permobil,
Puritan Bennett, Pride, Respironics, Ross,
Sammons Preston, Smith-Nephew, Sunrise Medical